

Key: NCTSzE_DE_OUT_XML_AI
XSD: interfaceDescription_NCTSzE_DE_OUT_XML_AI - 1.0.0.xsd
Document-Version: interfaceDescription_NCTSzE_DE_OUT_XML_AI - 1.0.0
Notes:

| | |
|----------------|---|
| 1 | Root |
| 1.1 | Root.Client |
| 1.2 | Root.CountryOfLodgement |
| 1.3 | Root.OperationDomain |
| 1.4 | Root.OperationType |
| 1.5 | Root.ID |
| 1.6 | Root.ReferenceNumber |
| 1.7 | Root.AdditionalReferenceNumber |
| 1.8 | Root.ConsignmentReferenceNumberAC |
| 1.9 | Root.Header |
| 1.9.1 | Root.Header.MRN |
| 1.10 | Root.Event |
| 1.10.1 | Root.Event.MessageName |
| 1.10.2 | Root.Event.MessageType |
| 1.10.3 | Root.Event.PreparationDateAndTime |
| 1.10.4 | Root.Event.PreparationDateAndTimeTimezone |
| 1.10.5 | Root.Event.Transition |
| 1.10.5.1 | Root.Event.Transition.E_DES_PER |
| 1.10.5.1.1 | Root.Event.Transition.E_DES_PER.DeclarationType |
| 1.10.5.1.2 | Root.Event.Transition.E_DES_PER.TIRCarnetNumber |
| 1.10.5.1.3 | Root.Event.Transition.E_DES_PER.DeclarationAcceptanceDate |
| 1.10.5.1.4 | Root.Event.Transition.E_DES_PER.LimitDate |
| 1.10.5.1.5 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure |
| 1.10.5.1.5.1 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.IdentificationNumber |
| 1.10.5.1.5.2 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.TIRHolderIdentificationNumber |
| 1.10.5.1.5.3 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Name |
| 1.10.5.1.5.4 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address |
| 1.10.5.1.5.4.1 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address.StreetAndNumber |
| 1.10.5.1.5.4.2 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address.Postcode |
| 1.10.5.1.5.4.3 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address.City |
| 1.10.5.1.5.4.4 | Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address.Country |
| 1.10.5.2 | Root.Event.Transition.E_DES_STA |
| 1.10.5.2.1 | Root.Event.Transition.E_DES_STA.DestinationStatus |
| 1.10.5.2.2 | Root.Event.Transition.E_DES_STA.Reason |
| 1.10.5.2.3 | Root.Event.Transition.E_DES_STA.ArrivalNotificationDateAndTime |
| 1.10.5.2.4 | Root.Event.Transition.E_DES_STA.ArrivalNotificationDateAndTimeTimezone |
| 1.10.5.2.5 | Root.Event.Transition.E_DES_STA.FinishingDateAndTime |
| 1.10.5.2.6 | Root.Event.Transition.E_DES_STA.FinishingDateAndTimeTimezone |
| 1.10.5.3 | Root.Event.Transition.E_DES_REJ |
| 1.10.5.3.1 | Root.Event.Transition.E_DES_REJ.BusinessRejectionType |
| 1.10.5.3.2 | Root.Event.Transition.E_DES_REJ.RejectionDateAndTime |
| 1.10.5.3.3 | Root.Event.Transition.E_DES_REJ.RejectionDateAndTimeTimezone |
| 1.10.5.3.4 | Root.Event.Transition.E_DES_REJ.RejectionCode |
| 1.10.5.3.5 | Root.Event.Transition.E_DES_REJ.RejectionReason |
| 1.10.5.3.6 | Root.Event.Transition.E_DES_REJ.Error |
| 1.10.5.3.6.1 | Root.Event.Transition.E_DES_REJ.Error.ErrorPointer |
| 1.10.5.3.6.2 | Root.Event.Transition.E_DES_REJ.Error.ErrorCode |
| 1.10.5.3.6.3 | Root.Event.Transition.E_DES_REJ.Error.ErrorText |
| 1.10.5.3.6.4 | Root.Event.Transition.E_DES_REJ.Error.OriginalAttributeValue |
| 1.10.5.4 | Root.Event.Transition.E_ERR_NCK |
| 1.10.5.4.1 | Root.Event.Transition.E_ERR_NCK.Error |
| 1.10.5.4.1.1 | Root.Event.Transition.E_ERR_NCK.Error.ErrorPointer |
| 1.10.5.4.1.2 | Root.Event.Transition.E_ERR_NCK.Error.ErrorCode |
| 1.10.5.4.1.3 | Root.Event.Transition.E_ERR_NCK.Error.ErrorText |
| 1.10.5.4.1.4 | Root.Event.Transition.E_ERR_NCK.Error.OriginalAttributeValue |
| 1.11 | Root.Attachment |
| 1.11.1 | Root.Attachment.Type |
| 1.11.2 | Root.Attachment.Filename |
| 1.11.3 | Root.Attachment.Content |

| Identifier | Required/Optional | Format | Iteration |
|--|-------------------|--------|-----------|
| 1 Root | K | | 1 - 1 |
| 1.1 Root.Client | K | ..8 | 1 - 1 |
| Client Identifier of the client where the operation is processed in AC. | | | |
| 1.2 Root.CountryOfLodgement | K | 2 | 1 - 1 |
| Country of lodgement ISO code of the country in which the operation is registered. | | | |
| 1.3 Root.OperationDomain | K | ..35 | 1 - 1 |
| Operation domain Identifier for the process of the operation in AC. The country of lodgement, the operation domain and the operation typ classify it. | | | |
| 1.4 Root.OperationType | K | ..35 | 1 - 1 |
| Operation type Identifier for the operation. | | | |
| 1.5 Root.ID | K | .. | 1 - 1 |
| ID The unique identifier of the operation. ID is the identification number created by AC after a transaction is registered. | | | |
| 1.6 Root.ReferenceNumber | O | ..50 | 0 - 1 |
| Reference number The reference number is the internal reference number of the declaration. | | | |
| 1.7 Root.AdditionalReferenceNumber | O | ..50 | 0 - 1 |
| Additional reference number An additional reference number that can be used for the technical identification of the transaction. (not mandatory) | | | |
| 1.8 Root.ConsignmentReferenceNumberAC | O | ..50 | 0 - 1 |
| AC Consignment reference number The consignment number of the operation. | | | |
| 1.9 Root.Header | K | | 1 - 1 |
| Header Overall details of the transaction | | | |
| 1.9.1 Root.Header.MRN | K | 18 | 1 - 1 |
| MRN The Master Reference Number is the internationally unique customs registration number for the transaction. | | | |
| 1.10 Root.Event | K | | 1 - 1 |
| Event The event is based on the ATLAS message received for the operation. | | | |
| 1.10.1 Root.Event.MessageName | K | 9 | 1 - 1 |
| Message name The functional ATLAS message name of the message. | | | |
| 1.10.2 Root.Event.MessageType | K | 6 | 1 - 1 |
| Message type The technical message type of the ATLAS message. | | | |
| 1.10.3 Root.Event.PreparationDateAndTime | K | .. | 1 - 1 |
| Date and time of preparation Time when the message was generated. | | | |
| 1.10.4 Root.Event.PreparationDateAndTimeTimezone | K | ..255 | 1 - 1 |
| Time zone Time zone at the previously mentioned date and time. | | | |

| Identifier | Required/Optional | Format | Iteration |
|--|-------------------|--------|-----------|
| 1.10.5 Root.Event.Transition | K | | 1 - 1 |
| Transition Field which AC internally uses to identify the current type of transition. It correlates to the type/name of the exchanged message. | | | |
| 1.10.5.1 Root.Event.Transition.E_DES_PER | K | | 1 - 1 |
| E_DES_PER Message unloading permission | | | |
| 1.10.5.1.1 Root.Event.Transition.E_DES_PER.DeclarationType | K | ..5 | 1 - 1 |
| Type of declaration ATLAS code list: C0231 Indication of the transit procedure under which the goods were carried. | | | |
| 1.10.5.1.2 Root.Event.Transition.E_DES_PER.TIRCarnetNumber | O | ..12 | 0 - 1 |
| Carnet TIR Number Identification number of the Carnet TIR process. | | | |
| 1.10.5.1.3 Root.Event.Transition.E_DES_PER.DeclarationAcceptanceDate | O | .. | 0 - 1 |
| Date of acceptance Date of acceptance of the declaration. | | | |
| 1.10.5.1.4 Root.Event.Transition.E_DES_PER.LimitDate | O | .. | 0 - 1 |
| Date of representation Date of the end of the time for representation at the customs office of destination or at the place of the authorised consignee. | | | |
| 1.10.5.1.5 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure | K | | 1 - 1 |
| Holder of the transit procedure | | | |
| 1.10.5.1.5.1 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.IdentificationNumber | O | ..17 | 0 - 1 |
| Identification number Indication of the EORI number of the holder of the transit procedure. | | | |
| 1.10.5.1.5.2 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.TIRHolderIdentificationNumber | O | ..17 | 0 - 1 |
| Identification number of the TIR-holder Indication of the identification number of the TIR-holder. | | | |
| 1.10.5.1.5.3 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Name | K | ..70 | 1 - 1 |
| Name Name or company name of the holder of the transit procedure | | | |
| 1.10.5.1.5.4 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address | K | | 1 - 1 |
| Address | | | |
| 1.10.5.1.5.4.1 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address.StreetAndNumber | K | ..70 | 1 - 1 |
| Street and number Street and number of the holder of the procedure. | | | |
| 1.10.5.1.5.4.2 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address.Postcode | O | ..17 | 0 - 1 |
| Postcode Postcode of the holder of the procedure. | | | |
| 1.10.5.1.5.4.3 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address.City | K | ..35 | 1 - 1 |
| City City of the holder of the procedure. | | | |
| 1.10.5.1.5.4.4 Root.Event.Transition.E_DES_PER.HolderOfTheTransitProcedure.Address.Country | K | 2 | 1 - 1 |
| Country ATLAS code list: C0248 Country code of the holder of the transit procedure. | | | |
| 1.10.5.2 Root.Event.Transition.E_DES_STA | K | | 1 - 1 |
| E_DES_STA Status message customs office of destination | | | |

| | | | |
|------------------------|------------------------------|--|-------------|
| Interface description: | NCTSzE_DE_OUT_XML_AI - 1.0.0 | Creation date 08.03.2023 Created by AC-0-p5536_20230307 | Page 5 of 6 |
|------------------------|------------------------------|--|-------------|

| Identifier | Required/Optional | Format | Iteration |
|--|-------------------|--------|-----------|
| 1.10.5.2.1 Root.Event.Transition.E_DES_STA.DestinationStatus | K | .. | 1 - 1 |
| Status of destination Status of the transit operation at the customs office of destination '311' = operation requested '343' = control result recorded '361' = Discharge completed | | | |
| 1.10.5.2.2 Root.Event.Transition.E_DES_STA.Reason | O | ..512 | 0 - 1 |
| Reason Textual information on the status of the transit operation. The information is given, if the status is '311'. | | | |
| 1.10.5.2.3 Root.Event.Transition.E_DES_STA.ArrivalNotificationDateAndTime | K | .. | 1 - 1 |
| Date and time of arrival notification Date and time of arrival at the authorised consignee (ZE/ZT) / presentation at the customs office of destination. | | | |
| 1.10.5.2.4 Root.Event.Transition.E_DES_STA.ArrivalNotificationDateAndTimeTimezone | K | ..255 | 1 - 1 |
| Time zone Time zone at the previously mentioned date and time. | | | |
| 1.10.5.2.5 Root.Event.Transition.E_DES_STA.FinishingDateAndTime | O | .. | 0 - 1 |
| Date and time of finishing Date and time of completion of the termination. The information is given at status '361'. | | | |
| 1.10.5.2.6 Root.Event.Transition.E_DES_STA.FinishingDateAndTimeTimezone | O | ..255 | 0 - 1 |
| Time zone Time zone at the previously mentioned date and time. | | | |
| 1.10.5.3 Root.Event.Transition.E_DES_REJ | K | | 1 - 1 |
| E_DES_REJ Rejection message | | | |
| 1.10.5.3.1 Root.Event.Transition.E_DES_REJ.BusinessRejectionType | K | .. | 1 - 1 |
| Type of rejection ATLAS code list: S0560 Rejection Trigger to understand various dependencies within the message, the content of code list S0570 is shown below. '007' Arrival comment not accepted '044' Unloading comment not accepted | | | |
| 1.10.5.3.2 Root.Event.Transition.E_DES_REJ.RejectionDateAndTime | K | .. | 1 - 1 |
| Date and time of rejection | | | |
| 1.10.5.3.3 Root.Event.Transition.E_DES_REJ.RejectionDateAndTimeTimezone | K | ..255 | 1 - 1 |
| Time zone Time zone at the previously mentioned date and time. | | | |
| 1.10.5.3.4 Root.Event.Transition.E_DES_REJ.RejectionCode | K | .. | 1 - 1 |
| Rejection code ATLAS code list: S0226 Type of rejection | | | |
| 1.10.5.3.5 Root.Event.Transition.E_DES_REJ.RejectionReason | O | ..512 | 0 - 1 |
| Reason of rejection Textual information on the reason for rejection. Indicated if the rejection type is '4'. | | | |
| 1.10.5.3.6 Root.Event.Transition.E_DES_REJ.Error | O | | 0 - 999 |
| Error | | | |
| 1.10.5.3.6.1 Root.Event.Transition.E_DES_REJ.Error.ErrorPointer | O | ..512 | 0 - 1 |
| Pointer Faulty data group or faulty data field in the message structure. | | | |
| 1.10.5.3.6.2 Root.Event.Transition.E_DES_REJ.Error.ErrorCode | K | 8 | 1 - 1 |
| Code Number and classification of the error message. | | | |

| Identifier | Required/Optional | Format | Iteration |
|--|---|--------|-----------|
| 1.10.5.3.6.3 Root.Event.Transition.E_DES_REJ.Error.ErrorText | K | ..512 | 1 - 1 |
| Text | | | |
| Description of the error | | | |
| 1.10.5.3.6.4 Root.Event.Transition.E_DES_REJ.Error.OriginalAttributeValue | O | ..512 | 0 - 1 |
| Original value | | | |
| Quoted value of the erroneous data field. Depending on the context and error, an original value can be quoted. | | | |
| 1.10.5.4 Root.Event.Transition.E_ERR_NCK | K | | 1 - 1 |
| E_ERR_NCK | | | |
| Error message | | | |
| 1.10.5.4.1 Root.Event.Transition.E_ERR_NCK.Error | K | | 1 - 9999 |
| Error information | | | |
| 1.10.5.4.1.1 Root.Event.Transition.E_ERR_NCK.Error.ErrorPointer | O | ..512 | 0 - 1 |
| Pointer | | | |
| Faulty data group or faulty data field in the message structure. | | | |
| 1.10.5.4.1.2 Root.Event.Transition.E_ERR_NCK.Error.ErrorCode | K | 8 | 1 - 1 |
| Code | | | |
| Number and classification of the error message. | | | |
| 1.10.5.4.1.3 Root.Event.Transition.E_ERR_NCK.Error.ErrorText | K | ..512 | 1 - 1 |
| Text | | | |
| Description of the error. | | | |
| 1.10.5.4.1.4 Root.Event.Transition.E_ERR_NCK.Error.OriginalAttributeValue | O | ..512 | 0 - 1 |
| Original value | | | |
| Quoted value of the erroneous data field. Depending on the context and error, an original value can be quoted. | | | |
| 1.11 Root.Attachment | O | | 0 - 9 |
| Attachment | | | |
| 1.11.1 Root.Attachment.Type | K | ..255 | 1 - 1 |
| Type | | | |
| Type of document | | | |
| Permitted values: | | | |
| ATLAS message | ATLAS message The attachment contains the original ATLAS XML message received from Customs. The ATLAS message is the trigger for this file. The attachment is base64 encoded. | | |
| 1.11.2 Root.Attachment.Filename | O | ..255 | 0 - 1 |
| File name | | | |
| 1.11.3 Root.Attachment.Content | K | .. | 1 - 1 |
| Content | | | |
| Base64-encoded file content of the file transmitted by customs. | | | |